

Maxx® Slash® (Model 102076-4) Parts List

Parts shown in bold are optional accessories. Part categories and individual part listings are arranged alphabetically.

| | Bearings & Bushings | 10244 7799 | Skidplate, front (1), rear (1) Tires, rubber (2) (fits Travvac® #7775Y wheelig har wheels) |
|---|---|----------------------|---|
| 3799 | Ball bearing kit, Maxx® (complete) | | Tires, rubber (2) (fits Traxxas® #7775X wheelie bar wheels) |
| 799X | Ball bearing kit, stainless steel, Maxx® (complete) | 10278 | Wheelie bar, assembled (fits Maxx® or Maxx Slash®) |
| 106A | Ball bearing, black rubber sealed (15x24x5mm) (2) | 7775 | Wheels, wheelie bar (2)/ axles, wheelie bar (2)/ 10x15x4 plastic |
| 107A | Ball Bearing, black rubber sealed (17x26x5) (2) | | bushings (4) (for #7776, 8976, or 9576 wheelie bar) |
| 099A | Ball bearing, black rubber sealed (17x26x6) (2) Ball bearing, black rubber sealed (6x16x5mm) (2) | 7775X | Wheels, wheelie bar, 6061-T6 aluminum (blue-anodized) (2)/ |
| 728 | Ball bearings (5x8x2.5mm) (2) | | axle, wheelie bar, 6061-T6 aluminum (2)/ 10x15x4 ball bearin |
| 119A | Ball bearings, black rubber sealed (10x15x4mm) (2) | 777EA | (4) |
| | • , , , | 7775A | Wheels, wheelie bar, 6061-T6 aluminum (dark titanium- |
| 120A | Ball bearings, black rubber sealed (12x18x4mm) (2) | | anodized) (2)/ axle, wheelie bar, 6061-T6 aluminum (2)/ 10x1 |
| 101A | Ball bearings, black rubber sealed (12x21x5mm) (2) | | ball bearings (4) |
| 098A | Ball bearings, black rubber sealed (17x23x4mm) (2) | 7775G | Wheels, wheelie bar, 6061-T6 aluminum (green-anodized) (2) |
| 180A | Ball bearings, black rubber sealed (6x13x5mm) (2) | | axle, wheelie bar, 6061-T6 aluminum (2)/ 10x15x4 ball bearin |
| 118A | Ball bearings, black rubber sealed (8x16x5mm) (2) | | (4) |
| 101 | Ball bearings, blue rubber sealed (12x21x5mm) (2) | 7775T | Wheels, wheelie bar, 6061-T6 aluminum (orange-anodized) (|
| 020 | Ball bearings, blue rubber sealed (8x12x3.5mm) (2) | • | axle, wheelie bar, 6061-T6 aluminum (2)/ 10x15x4 ball bearin |
| | Body & Accessories | 7775R | (4) Wheels wheelig her 6064 T6 aluminum (red anadized) (2)/ |
| 2226 | | IIIOK | Wheels, wheelie bar, 6061-T6 aluminum (red-anodized) (2)/ |
| 0226 | Body reinforcement set, black/ 3x10mm CS (8) (fits #10211 body) | | axle, wheelie bar, 6061-T6 aluminum (2)/ 10x15x4 ball bearin |
| 0224 | Body reinforcement set, black/ skid pads (roof)/ 3x10mm CS (14) | | (4) |
| 2040 | (fits #10211 body) | | Cush Drive Components |
| 0216 | Body reinforcement set, front (left & right) (attaches to #10211 | 6465 | Cush drive key/ pin/ elastomer damper |
| | body) | 7793X | Housing, cush drive (front & rear halves) |
| 0217 | Body reinforcement set, rear (left & right) (attaches to #10211 body) | | Spur gear, 46-tooth (machined, hardened steel) (wide face, 1 |
| 0213 | Body support (fits #10211 body) | 6442 | • |
| 0219 | Body support, side/ mount (left & right) (for #10211 body) | 6447R | metric pitch) Spur goar 46 tooth stool (wide face 1.0 metric pitch) |
| 0211 | Body, Maxx Slash® (clear, requires painting)/ window masks/ | | Spur gear, 46-tooth, steel (wide-face, 1.0 metric pitch) |
| | decal sheet (includes body support, body plastics, latches, & | 6443 | Spur gear, 50-tooth (machined, hardened steel) (wide face, 1 |
| | hardware for clipless mounting) | 04400 | metric pitch) |
| 0211R | Body, Maxx Slash® (clear, requires painting)/ window masks/ | 6448R | Spur gear, 50-tooth, steel (wide-face, 1.0 metric pitch) |
| | decal sheet (includes body support, body plastics, latches, & | 6444 | Spur gear, 54-tooth (machined, hardened steel) (wide face, 1 |
| | hardware for clipless mounting) (heavy duty) | | metric pitch) |
| 0211-BLUE | Body, Maxx Slash®, blue (painted)/ decal sheet (assembled with | 6449R | Spur gear, 54-tooth, steel (wide-face, 1.0 metric pitch) |
| | body support, body plastics, & latches for clipless mounting) | | Differential Components |
| 0211-GRN | Body, Maxx Slash®, green (painted)/ decal sheet (assembled with | 10001 | |
| | body support, body plastics, & latches for clipless mounting) | 10281 | Carrier, differential (aluminum)/ o-ring gaskets (2)/ ring gear gasl |
| 0211X | Body, Maxx Slash®, ProGraphix® (graphics are printed, | | spacers (4)/ 12.2x18x0.5 MW/ 3x15mm flat-head machine screw |
| | requires paint & final color application)/ decal sheet (includes | 0004 | (with threadlock) (4) |
| | body support, body plastics, latches, & hardware for clipless | 8981 | Carrier, differential/ x-ring gasket/ o-ring (2)/ 10x19.5x0.5 TW |
| | mounting) | 10280A | Differential kit, center (complete) (aluminum carrier, 100K wt |
| 0211-RED | Body, Maxx Slash®, red (painted)/ decal sheet (assembled with | | differential fluid) (fits Maxx® or Maxx® Slash®) |
| | body support, body plastics, & latches for clipless mounting) | 10280X | Differential kit, center (complete) (aluminum carrier, 20MM v |
| 0211-RNR | Body, Maxx Slash®, Rock n' Roll (painted)/ decal sheet (assembled | | differential fluid) (fits Maxx® or Maxx® Slash®) |
| 02 | with body support, body plastics, & latches for clipless mounting) | 5136X | Differential oil kit (1 each: 10K, 30K, 50K weights) |
| 0218 | Latch, body mount (4) (for clipless body mounting) (attaches to | 8949 | Differential output yoke assembly, front or rear (assembled with |
| 02.0 | #10211 body) | | external-splined half shaft) |
| 0225 | Skid pads (roof)/ retainers (2)/ 3x10mm CS (6) (fits #10211 body) | 10249 | Differential output yoke assembly, front or rear, Maxx® Duty stee |
| 0220 | | Ī | core (1) (assembled with external-splined half shaft) |
| | Bumpers & Skidplates | 8982 | Gear set, differential (output gears (2)/ spider gears (4)/ spider g |
| 0233 | Bumper mount, front | _ | shaft (2)/ output shaft (2)/ 2.5x13.8 pin (2)) |
| 0235 | Bumper, front | 8988 | Gear, center differential, 44-tooth |
| 0236 | Bumper, rear | 5041 | Grease, premium high performance (20cc) |
| 0245 | Skidplate, center/ 4x30 CCS (4)/ 3x10 CS (4) | 8985 | Input gear, transmission, 22-tooth/ 2.5x12mm pin |
| 0244 | Skidplate, front (1), rear (1) | 8986 | Input shaft, transmission |
|)Z 44 | | 5130 | Oil, differential (100K wt) (0.7 oz (20cc)) |
| | Chassis & Attachments | 5135 | Oil, differential (10K wt) (1.7 oz (50cc)) |
|)215 | Body mounts, front (left & right) (for clipless body mounting) | | |
|)214 | Body mounts, rort (left & right) (for clipless body mounting) | 5040 | Oil, differential (20M wt) (standard) |
| | | 5136 | Oil, differential (30K wt) (1.7 oz (50cc)) |
| 0216 | Body reinforcement set, front (left & right) (attaches to #10211 | 5137 | Oil, differential (50K wt) (1.7 oz (50cc)) |
| 1217 | body) Pody reinfercement set rear (left & right) (attaches to #10211 healy) | 8989X | Output gear, center differential, hardened steel (2) |
| 0217 | Body reinforcement set, rear (left & right) (attaches to #10211 body) | 8978 | Ring gear, differential/ pinion gear, differential (front) |
| 924 | Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ | 8977 | Ring gear, differential/ pinion gear, differential (rear) |
| 2000 | 2.5x10 CS (2)/ 3x10 CCS (3) | | Driveline Components |
| 0233 | Bumper mount, front | 005637 | |
| 0235 | Bumper, front | 8952X | Carriers, stub axle (blue-anodized 6061-T6 aluminum) (rear) |
| 0236 | Bumper, rear | 8952G | Carriers, stub axle (green-anodized 6061-T6 aluminum) (real |
| 0222 | Chassis | | (2) |
| 921 | Chassis brace, front | 8952 | Carriers, stub axle (left & right) |
| 987 | Covers, gear (2) | 8952A | Carriers, stub axle (orange-anodized 6061-T6 aluminum) (re |
| | Hold down, battery | | (2) |
| | Motor mount cap | 8952R | Carriers, stub axle (red-anodized 6061-T6 aluminum) (rear) (|
| 627 | | 10249 | Differential output yoke assembly, front or rear, Maxx® Duty stee |
| 627 0260 | · | | , |
| 627 0260 0223 | Nerf bars, chassis (2) | | core (1) (assembled with external-splined half shaft) |
| 627 0260 0223 628 | Nerf bars, chassis (2) Retainer, battery hold-down (front and rear) (1 each) | | . , . |
| 627 0260 0223 628 925 | Nerf bars, chassis (2) Retainer, battery hold-down (front and rear) (1 each) Seal kit, receiver box (includes o-ring, seal, and silicone grease) | 8951 | Drive cup (1)/ 4x15.8mm screw pin (1) (for #8950X or 8996X |
| 627 0260 0223 628 925 938X | Nerf bars, chassis (2) Retainer, battery hold-down (front and rear) (1 each) Seal kit, receiver box (includes o-ring, seal, and silicone grease) Shock tower, front (left & right halves) | 8951 | Drive cup (1)/ 4x15.8mm screw pin (1) (for #8950X or 8996X steel CV driveshafts) |
| 627 0260 0223 628 925 | Nerf bars, chassis (2) Retainer, battery hold-down (front and rear) (1 each) Seal kit, receiver box (includes o-ring, seal, and silicone grease) | | Drive cup (1)/ 4x15.8mm screw pin (1) (for #8950X or 8996X |

| Page 2 | Maxx® Slash®: | TQi™ Traxxas | Link™ Enabled 2. | 4GHz Radio & TSI | M® (Model 102076-4) | Parts List |
|--------|---------------|--------------|------------------|------------------|---------------------|------------|
| | | | | | | |

| 10250 | Driveshaft assembly, front or rear, Maxx® Duty steel core (left or right) (1) (fully assembled, ready to install)/ screw pin (1) | 8929G 8929T | Suspension arms, upper, green (left or right, front or rear) (2) Suspension arms, upper, orange (left or right, front or rear) (2) |
|--|---|--|--|
| 10255 | Driveshaft, center, aluminum | 8929R | Suspension arms, upper, red (left or right, front or rear) (2) |
| 8950A | Driveshaft, steel constant-velocity (shaft only, 89.5mm) (1) (for use only with #8951 drive cup) | 8929A | Suspension arms, upper, white (left or right, front or rear) (2) |
| 8950X | Driveshafts, steel constant-velocity (assembled), front or rear | 7743 7743-BLUE | Suspension pin retainer (4) |
| 00000 | (4) (#8654, 8654G, or 8654R and #7758, 7758G, or 7758R | 7743-GRAY | Suspension pin retainer, 6061-T6 aluminum (blue-anodized) (4) Suspension pin retainer, 6061-T6 aluminum (gray-anodized) (4) |
| | required for a complete set) | 7743-GRA1 | Suspension pin retainer, 6061-T6 aluminum (green-anodized) |
| 8447A | Nuts, 5mm flanged nylon locking (aluminum, black-anodized, | 7740-0111 | (4) |
| | serrated) (4) | 7743-ORNG | • • |
| 8447X | Nuts, 5mm flanged nylon locking (aluminum, blue-anodized, | | (4) |
| 8447G | serrated) (4) | 7743-RED | Suspension pin retainer, 6061-T6 aluminum (red-anodized) (4) |
| 0447G | Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4) | 8940X | Suspension pin set, complete (hardened steel), 4x64mm (4), |
| 8447R | Nuts, 5mm flanged nylon locking (aluminum, red-anodized, | | 4x22mm (4), 4x38mm (4), 4x33mm (4), 4x47mm (4)/ 3x8mm BCS (14)/ 3x6mm BCS (4)/ retainers (8) |
| | serrated) (4) | 8942 | Suspension pin set, front (left or right) (hardened steel), |
| 8447 | Nuts, 5mm flanged nylon locking (steel, black serrated) (8) | 00-12 | 4x64mm (1), 4x22mm (2), 4x38mm (1), 4x33mm (1), 4x47mm (1) |
| 5040 | Oil, differential (20M wt) (standard) | 8941 | Suspension pins, lower, inner (front or rear), 4x64mm (2) (hardened |
| 10253 | Stub axle assembly, outer, Maxx® Duty (front or rear) (steel) (1) | | steel) |
| 8956 | Wheel hubs, hex (2)/ 2.5x14 pins (2) | 8940 | Suspension screw pin set, front or rear (hardened steel), 4x18mm |
| 8956X | Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw pins (4) | 8948X | (4), 4x38mm (2), 4x33mm (2), 4x43mm (2) Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, |
| 8956G | Wheel hubs, hex, aluminum (green-anodized) (4)/ 4x13mm | 09407 | stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod |
| | screw pins (4) | | ends, front (4)/ aluminum wrench (1) |
| 8956T | Wheel hubs, hex, aluminum (orange-anodized) (4)/ 4x13mm | 8948G | Toe links, front (TUBES green-anodized, 7075-T6 aluminum, |
| | screw pins (4) | | stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod |
| 8956R | Wheel hubs, hex, aluminum (red-anodized) (4)/ 4x13mm screw | 00404 | ends, front (4)/ aluminum wrench (1) |
| 8654 | pins (4) Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), | 8948A | Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod |
| 0007 | 3x14mm pin (4) | | ends, front (4)/ aluminum wrench (1) |
| 8654-GRAY | · · · · | 8948R | Toe links, front (TUBES red-anodized, 7075-T6 aluminum, |
| | 3x14mm pin (4) | | stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod |
| 8654G | Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), | | ends, front (4)/ aluminum wrench (1) |
| 00544 | 3x14mm pin (4) | | Hardware |
| 8654A | Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5mm GS (4)/ 3x14mm pin (4) | 1552 | 3x8mm Hex Cap Screws (6)/ Washers (6)/ Wrench (1) |
| 8654R | Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), | 3642 | Attachment screws, shock (3x12mm shoulder screws) (6) |
| | 3x14mm pin (4) | 4859 | CS 3x10 flathead (hex drive) |
| 10257 | Wheel washers (4) | 2584 | Head screws, 3x12mm cap-head machine (hex drive) (6) (TRX® |
| 8957 | Wheel washers (4) | 8447A | 2.5, 2.5R, 3.3) Nuts, 5mm flanged nylon locking (aluminum, black-anodized, |
| 8957X 8957G | Wheel washers, blue (4) | 01111 | serrated) (4) |
| 8957G 8957T | Wheel washers, green (4) Wheel washers, orange (4) | 8447X | Nuts, 5mm flanged nylon locking (aluminum, blue-anodized, |
| 8957R | Wheel washers, red (4) | | serrated) (4) |
| | | 8447G | Nuts, 5mm flanged nylon locking (aluminum, green-anodized, |
| | Frant Suchencian o Steering | | |
| 9026 | Front Suspension & Steering Rulkhard tie ber front upper (AV Joyce (2) (steel) | | serrated) (4) |
| 8926 8920 | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) | 8447R | |
| 8920 | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) Bulkhead, front (upper and lower) | | serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, |
| | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) | 8447R 8447 5147X | serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Nuts, 5mm flanged nylon locking (steel, serrated) (8) |
| 8920 | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) Bulkhead, front (upper and lower) Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), | 8447 R 8447 5147X 3236 | serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Nuts, 5mm flanged nylon locking (steel, serrated) (8) Screws, 2.5x12mm cap-head machine (6) |
| 8920 8932X 8932G | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) Bulkhead, front (upper and lower) Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) | 8447R 8447 5147X 3236 2577 | serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Nuts, 5mm flanged nylon locking (steel, serrated) (8) Screws, 2.5x12mm cap-head machine (6) Screws, 3x10mm button-head machine (hex drive) (6) |
| 8920 8932X | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) Bulkhead, front (upper and lower) Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized), | 8447R 8447 5147X 3236 2577 2587 | serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Nuts, 5mm flanged nylon locking (steel, serrated) (8) Screws, 2.5x12mm cap-head machine (6) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x10mm caphead machine (6) (no washer) |
| 8920 8932X 8932G 8932A | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) Bulkhead, front (upper and lower) Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) | 8447R 8447 5147X 3236 2577 2587 2551 | serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Nuts, 5mm flanged nylon locking (steel, serrated) (8) Screws, 2.5x12mm cap-head machine (6) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x10mm caphead machine (6) (no washer) Screws, 3x10mm countersunk machine (6) (hex drive) |
| 8920 8932X 8932G | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) Bulkhead, front (upper and lower) Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left | 8447R 8447 5147X 3236 2577 2587 2551 2578 | serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Nuts, 5mm flanged nylon locking (steel, serrated) (8) Screws, 2.5x12mm cap-head machine (6) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x10mm caphead machine (6) (no washer) Screws, 3x10mm countersunk machine (6) (hex drive) Screws, 3x12mm button-head machine (hex drive) (6) |
| 8920 8932X 8932G 8932A | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) Bulkhead, front (upper and lower) Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) | 8447R 8447 5147X 3236 2577 2587 2551 2578 2579 | serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Nuts, 5mm flanged nylon locking (steel, serrated) (8) Screws, 2.5x12mm cap-head machine (6) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x10mm caphead machine (6) (no washer) Screws, 3x10mm countersunk machine (6) (hex drive) |
| 8920 8932X 8932G 8932A 8932R | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) Bulkhead, front (upper and lower) Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), left & right Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or | 8447R 8447 5147X 3236 2577 2587 2551 2578 | serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Nuts, 5mm flanged nylon locking (steel, serrated) (8) Screws, 2.5x12mm cap-head machine (6) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x10mm caphead machine (6) (no washer) Screws, 3x10mm countersunk machine (6) (hex drive) Screws, 3x12mm button-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6) |
| 8920 8932X 8932G 8932A 8932R 8932 8916 | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) Bulkhead, front (upper and lower) Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), left & right Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear (2) | 8447R 8447 5147X 3236 2577 2587 2551 2578 2579 2553 3646 2583 | serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Nuts, 5mm flanged nylon locking (steel, serrated) (8) Screws, 2.5x12mm cap-head machine (6) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x10mm caphead machine (6) (no washer) Screws, 3x10mm countersunk machine (6) (hex drive) Screws, 3x12mm button-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x15mm countersunk machine (6) (hex drive) Screws, 3x15mm flat-head machine (hex drive) (6) Screws, 3x18 button-head machine (hex drive) (6) |
| 8920 8932X 8932G 8932A 8932R 8932 | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) Bulkhead, front (upper and lower) Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), left & right Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear (2) Rod ends (4) (assembled with steel pivot balls) (replacement | 8447R 8447 5147X 3236 2577 2587 2551 2578 2579 2553 3646 2583 2581 | serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Nuts, 5mm flanged nylon locking (steel, serrated) (8) Screws, 2.5x12mm cap-head machine (6) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x10mm caphead machine (6) (no washer) Screws, 3x10mm countersunk machine (6) (hex drive) Screws, 3x12mm button-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x15mm flat-head machine (hex drive) (6) Screws, 3x18 button-head machine (hex drive) (6) Screws, 3x25mm button-head machine (hex drive) (6) |
| 8920 8932X 8932G 8932A 8932R 8932 8916 | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) Bulkhead, front (upper and lower) Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), left & right Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear (2) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X, | 8447R 8447 5147X 3236 2577 2587 2551 2578 2579 2553 3646 2583 2581 2582 | serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Nuts, 5mm flanged nylon locking (steel, serrated) (8) Screws, 2.5x12mm cap-head machine (6) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x10mm caphead machine (6) (no washer) Screws, 3x10mm countersunk machine (6) (hex drive) Screws, 3x12mm button-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x15mm flat-head machine (hex drive) (6) Screws, 3x18 button-head machine (hex drive) (6) Screws, 3x25mm button-head machine (hex drive) (6) Screws, 3x30mm button-head machine (hex drive) (6) |
| 8920 8932X 8932G 8932A 8932R 8932 8916 | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) Bulkhead, front (upper and lower) Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), left & right Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear (2) Rod ends (4) (assembled with steel pivot balls) (replacement | 8447R 8447 5147X 3236 2577 2587 2551 2578 2579 2553 3646 2583 2581 2582 2657 | serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Nuts, 5mm flanged nylon locking (steel, serrated) (8) Screws, 2.5x12mm cap-head machine (6) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x10mm caphead machine (6) (no washer) Screws, 3x10mm countersunk machine (6) (hex drive) Screws, 3x12mm button-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x15mm flat-head machine (hex drive) (6) Screws, 3x15mm flat-head machine (hex drive) (6) Screws, 3x25mm button-head machine (hex drive) (6) Screws, 3x30mm button-head machine (hex drive) (6) Screws, 3x30mm button-head machine (hex drive) (6) Screws, 3x8mm caphead machine (hex drive) (6) |
| 8920 8932X 8932G 8932A 8932R 8932 8916 | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) Bulkhead, front (upper and lower) Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), left & right Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear (2) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X, 8997A, 8997G, 8997R, 8997X) | 8447R 8447 5147X 3236 2577 2587 2551 2578 2579 2553 3646 2583 2581 2582 2657 2550 | serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Nuts, 5mm flanged nylon locking (steel, serrated) (8) Screws, 2.5x12mm cap-head machine (6) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x10mm caphead machine (6) (no washer) Screws, 3x10mm countersunk machine (6) (hex drive) Screws, 3x12mm button-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x15mm countersunk machine (6) (hex drive) Screws, 3x15mm flat-head machine (hex drive) (6) Screws, 3x15mm flat-head machine (hex drive) (6) Screws, 3x25mm button-head machine (hex drive) (6) Screws, 3x30mm button-head machine (hex drive) (6) Screws, 3x8mm caphead machine (hex drive) (6) Screws, 3x8mm countersunk machine (6) (hex drive) |
| 8920 8932X 8932G 8932A 8932R 8932 8916 8958 | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) Bulkhead, front (upper and lower) Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), left & right BCS (4)/ retainers (4) Caster blocks (c-hubs), left & right Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear (2) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X, 8997A, 8997G, 8997R, 8997X) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Shock tower, front (left & right halves) | 8447R 8447 5147X 3236 2577 2587 2551 2578 2579 2553 3646 2583 2581 2582 2657 2550 3936 | serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Nuts, 5mm flanged nylon locking (steel, serrated) (8) Screws, 2.5x12mm cap-head machine (6) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x10mm caphead machine (6) (no washer) Screws, 3x10mm countersunk machine (6) (hex drive) Screws, 3x12mm button-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x15mm flat-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x25mm button-head machine (hex drive) (6) Screws, 3x30mm button-head machine (hex drive) (6) Screws, 3x30mm button-head machine (hex drive) (6) Screws, 3x8mm caphead machine (hex drive) (6) Screws, 3x8mm countersunk machine (6) (hex drive) Screws, 4x10mm button-head machine (hex drive) (6) |
| 8920 8932X 8932G 8932A 8932R 8932 8916 8958 | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) Bulkhead, front (upper and lower) Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), left & right Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear (2) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X, 8997A, 8997G, 8997R, 8997X) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Shock tower, front (left & right halves) Steering bellcranks/ bellcrank support/ servo saver/ servo saver | 8447R 8447 5147X 3236 2577 2587 2551 2578 2579 2553 3646 2583 2581 2582 2657 2550 | serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Nuts, 5mm flanged nylon locking (steel, serrated) (8) Screws, 2.5x12mm cap-head machine (6) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x10mm caphead machine (6) (no washer) Screws, 3x10mm countersunk machine (6) (hex drive) Screws, 3x12mm button-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x15mm countersunk machine (6) (hex drive) Screws, 3x15mm flat-head machine (hex drive) (6) Screws, 3x15mm flat-head machine (hex drive) (6) Screws, 3x25mm button-head machine (hex drive) (6) Screws, 3x30mm button-head machine (hex drive) (6) Screws, 3x8mm caphead machine (hex drive) (6) Screws, 3x8mm countersunk machine (6) (hex drive) |
| 8920 8932X 8932G 8932A 8932R 8932 8916 8958 8947 | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) Bulkhead, front (upper and lower) Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), left & right Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear (2) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X, 8997A, 8997G, 8997R, 8997X) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Shock tower, front (left & right halves) Steering belicranks/ belicrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) | 8447R 8447 5147X 3236 2577 2587 2551 2578 2579 2553 3646 2583 2581 2582 2657 2550 3936 2535 3937 3938 | serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Nuts, 5mm flanged nylon locking (steel, serrated) (8) Screws, 2.5x12mm cap-head machine (6) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x10mm caphead machine (6) (no washer) Screws, 3x10mm countersunk machine (6) (hex drive) Screws, 3x12mm button-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x15mm countersunk machine (6) (hex drive) Screws, 3x15mm flat-head machine (hex drive) (6) Screws, 3x25mm button-head machine (hex drive) (6) Screws, 3x30mm button-head machine (hex drive) (6) Screws, 3x8mm caphead machine (hex drive) (6) Screws, 3x8mm countersunk machine (6) (hex drive) Screws, 4x10mm button-head machine (hex drive) (6) Screws, 4x10mm button-head machine (hex drive) (6) |
| 8920 8932X 8932G 8932A 8932R 8932 8916 8958 8947 8938X 8946 8937X | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) Bulkhead, front (upper and lower) Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), left & right Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear (2) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X, 8997A, 8997G, 8997R, 8997X) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Shock tower, front (left & right halves) Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering blocks, 6061-T6 aluminum (blue-anodized), left & right | 8447R 8447 5147X 3236 2577 2587 2551 2578 2579 2553 3646 2583 2581 2582 2657 2550 3936 2535 3937 3938 3933 | serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Nuts, 5mm flanged nylon locking (steel, serrated) (8) Screws, 2.5x12mm cap-head machine (6) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x10mm caphead machine (6) (no washer) Screws, 3x10mm countersunk machine (6) (hex drive) Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x15mm countersunk machine (6) (hex drive) Screws, 3x15mm flat-head machine (hex drive) (6) Screws, 3x25mm button-head machine (hex drive) (6) Screws, 3x25mm button-head machine (hex drive) (6) Screws, 3x30mm button-head machine (hex drive) (6) Screws, 3x8mm caphead machine (hex drive) (6) Screws, 4x10mm button-head machine (hex drive) (6) Screws, 4x10mm countersunk machine (hex drive) (6) Screws, 4x10mm button-head machine (hex drive) (6) Screws, 4x14mm button-head machine (hex drive) (6) Screws, 4x14mm button-head machine (hex drive) (6) Screws, 4x16mm button-head machine (hex drive) (6) |
| 8920 8932X 8932G 8932A 8932R 8932 8916 8958 8947 | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) Bulkhead, front (upper and lower) Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), left & right Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear (2) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X, 8997A, 8997G, 8997R, 8997X) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Shock tower, front (left & right halves) Steering belicranks/ belicrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) | 8447R 8447 5147X 3236 2577 2587 2551 2578 2579 2553 3646 2583 2581 2582 2657 2550 3936 2535 3937 3938 3933 2589 | serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Nuts, 5mm flanged nylon locking (steel, serrated) (8) Screws, 2.5x12mm cap-head machine (6) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x10mm caphead machine (6) (no washer) Screws, 3x10mm countersunk machine (6) (hex drive) Screws, 3x12mm button-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x15mm countersunk machine (hex drive) (6) Screws, 3x15mm flat-head machine (hex drive) (6) Screws, 3x18 button-head machine (hex drive) (6) Screws, 3x25mm button-head machine (hex drive) (6) Screws, 3x30mm button-head machine (hex drive) (6) Screws, 3x8mm caphead machine (hex drive) (6) Screws, 4x10mm button-head machine (hex drive) (6) Screws, 4x10mm countersunk machine (hex drive) (6) Screws, 4x10mm button-head machine (hex drive) (6) Screws, 4x14mm button-head machine (hex drive) (6) Screws, 4x14mm button-head machine (hex drive) (6) Screws, 4x16mm button-head machine (hex drive) (6) Screws, 4x10mm button-head machine (hex drive) (6) Screws, 4x10mm button-head machine (hex drive) (6) |
| 8920 8932X 8932G 8932A 8932R 8932 8916 8958 8947 8938X 8946 8937X | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) Bulkhead, front (upper and lower) Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), left & right Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear (2) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X, 8997A, 8997G, 8997R, 8997X) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Shock tower, front (left & right halves) Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right | 8447R 8447 5147X 3236 2577 2587 2551 2578 2579 2553 3646 2583 2581 2582 2657 2550 3936 2535 3937 3938 3937 3938 3933 2589 2455 | serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Nuts, 5mm flanged nylon locking (steel, serrated) (8) Screws, 2.5x12mm cap-head machine (6) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x10mm caphead machine (6) (no washer) Screws, 3x10mm countersunk machine (6) (hex drive) Screws, 3x12mm button-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x15mm countersunk machine (6) (hex drive) Screws, 3x15mm flat-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x25mm button-head machine (hex drive) (6) Screws, 3x30mm button-head machine (hex drive) (6) Screws, 3x30mm button-head machine (hex drive) (6) Screws, 3x8mm countersunk machine (6) (hex drive) Screws, 4x10mm button-head machine (hex drive) (6) Screws, 4x12mm button-head machine (hex drive) (6) Screws, 4x14mm button-head machine (hex drive) (6) Screws, 4x14mm button-head machine (hex drive) (6) Screws, 4x24mm button-head machine (hex drive) (6) Screws, 4x24mm button-head machine (hex drive) (6) Screws, 4x24mm button-head machine (hex drive) (6) |
| 8920 8932X 8932G 8932A 8932R 8932 8916 8958 8947 8938X 8946 8937X 8937G | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) Bulkhead, front (upper and lower) Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), left & right Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear (2) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X, 8997A, 8997G, 8997R, 8997X) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Shock tower, front (left & right halves) Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right | 8447R 8447 5147X 3236 2577 2587 2551 2578 2559 2553 3646 2583 2581 2582 2657 2550 3936 2535 3937 3938 3937 3938 3933 2589 2455 2596 | serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Nuts, 5mm flanged nylon locking (steel, serrated) (8) Screws, 2.5x12mm cap-head machine (6) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x10mm caphead machine (6) (no washer) Screws, 3x10mm countersunk machine (6) (hex drive) Screws, 3x12mm button-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x15mm flat-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x25mm button-head machine (hex drive) (6) Screws, 3x30mm button-head machine (hex drive) (6) Screws, 3x8mm caphead machine (hex drive) (6) Screws, 3x8mm countersunk machine (6) (hex drive) Screws, 4x10mm button-head machine (hex drive) (6) Screws, 4x12mm button-head machine (hex drive) (6) Screws, 4x14mm button-head machine (hex drive) (6) Screws, 4x16mm button-head machine (hex drive) (6) Screws, 4x26mm button-head machine (hex drive) (6) Screws, 4x25mm button-head machine (hex drive) (6) |
| 8920 8932X 8932G 8932A 8932R 8932 8916 8958 8947 8938X 8946 8937X 8937G 8937A | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) Bulkhead, front (upper and lower) Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), left & right Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear (2) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X, 8997A, 8997G, 8997R, 8997X) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Shock tower, front (left & right halves) Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right | 8447R 8447 5147X 3236 2577 2587 2551 2578 2579 2553 3646 2583 2581 2582 2657 2550 3936 2535 3937 3938 3933 2589 2455 2596 2595 | serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Nuts, 5mm flanged nylon locking (steel, serrated) (8) Screws, 2.5x12mm cap-head machine (6) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x10mm caphead machine (6) (no washer) Screws, 3x10mm countersunk machine (6) (hex drive) Screws, 3x12mm button-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x15mm countersunk machine (6) (hex drive) Screws, 3x15mm dat-head machine (hex drive) (6) Screws, 3x25mm button-head machine (hex drive) (6) Screws, 3x25mm button-head machine (hex drive) (6) Screws, 3x8mm caphead machine (hex drive) (6) Screws, 3x8mm countersunk machine (6) (hex drive) Screws, 4x10mm button-head machine (hex drive) (6) Screws, 4x12mm button-head machine (hex drive) (6) Screws, 4x16mm button-head machine (hex drive) (6) Screws, 4x16mm button-head machine (hex drive) (6) Screws, 4x20mm button-head machine (hex drive) (6) Screws, 4x24mm button-head machine (hex drive) (6) Screws, 4x25mm button-head machine (hex drive) (6) Screws, 4x25mm button-head machine (hex drive) (6) |
| 8920 8932X 8932G 8932A 8932R 8932 8916 8958 8947 8938X 8946 8937X 8937G 8937A | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) Bulkhead, front (upper and lower) Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), left & right Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear (2) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X, 8997A, 8997G, 8997R, 8997X) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Shock tower, front (left & right halves) Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right | 8447R 8447 5147X 3236 2577 2587 2551 2578 2559 2553 3646 2583 2581 2582 2657 2550 3936 2535 3937 3938 3937 3938 3933 2589 2455 2596 | serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Nuts, 5mm flanged nylon locking (steel, serrated) (8) Screws, 2.5x12mm cap-head machine (6) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x10mm caphead machine (6) (no washer) Screws, 3x10mm countersunk machine (6) (hex drive) Screws, 3x12mm button-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x15mm flat-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x25mm button-head machine (hex drive) (6) Screws, 3x30mm button-head machine (hex drive) (6) Screws, 3x8mm caphead machine (hex drive) (6) Screws, 3x8mm countersunk machine (6) (hex drive) Screws, 4x10mm button-head machine (hex drive) (6) Screws, 4x12mm button-head machine (hex drive) (6) Screws, 4x14mm button-head machine (hex drive) (6) Screws, 4x16mm button-head machine (hex drive) (6) Screws, 4x26mm button-head machine (hex drive) (6) Screws, 4x25mm button-head machine (hex drive) (6) |
| 8920 8932X 8932G 8932A 8932R 8932 8916 8958 8947 8938X 8946 8937X 8937G 8937A 8937R 8937 10230 | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) Bulkhead, front (upper and lower) Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), left & right Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear (2) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X, 8997A, 8997G, 8997R, 8997X) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Shock tower, front (left & right halves) Steering belicranks/ belicrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right | 8447R 8447 5147X 3236 2577 2587 2551 2578 2579 2553 3646 2583 2581 2582 2657 2550 3936 2535 3937 3938 3933 2589 2455 2596 2595 8940X | serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Nuts, 5mm flanged nylon locking (steel, serrated) (8) Screws, 2.5x12mm cap-head machine (6) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x10mm caphead machine (6) (no washer) Screws, 3x10mm countersunk machine (6) (hex drive) Screws, 3x12mm button-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x15mm countersunk machine (6) (hex drive) Screws, 3x15mm flat-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x25mm button-head machine (hex drive) (6) Screws, 3x30mm button-head machine (hex drive) (6) Screws, 3x30mm button-head machine (hex drive) (6) Screws, 3x8mm countersunk machine (hex drive) (6) Screws, 4x10mm button-head machine (hex drive) (6) Screws, 4x12mm button-head machine (hex drive) (6) Screws, 4x14mm button-head machine (hex drive) (6) Screws, 4x25mm button-head machine (hex drive) (6) Screws, 4x35mm button-head machine (hex drive) (6) Screws, 4x35mm button-head machine (hex drive) (6) Suspension pin set, complete (hardened steel), 4x64mm (4), 4x22mm (4), 4x38mm (4), 4x33mm (4), 4x47mm (4)/ 3x8mm BCS (14)/ 3x6mm BCS (4)/ retainers (8) |
| 8920 8932X 8932G 8932A 8932R 8932 8916 8958 8947 8938X 8946 8937X 8937G 8937A 8937A 8937R 8937 10230 10230-BLUI | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) Bulkhead, front (upper and lower) Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), left & right Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear (2) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X, 8997A, 8997G, 8997R, 8997X) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Shock tower, front (left & right halves) Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Suspension arms, lower, black (left and right, front or rear) (2) | 8447R 8447 5147X 3236 2577 2587 2551 2578 2579 2553 3646 2583 2581 2582 2657 2550 3936 2535 3937 3938 3933 2589 2455 2596 2595 | serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Nuts, 5mm flanged nylon locking (steel, serrated) (8) Screws, 2.5x12mm cap-head machine (6) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x10mm caphead machine (6) (no washer) Screws, 3x10mm countersunk machine (6) (hex drive) Screws, 3x12mm button-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x15mm countersunk machine (hex drive) (6) Screws, 3x15mm flat-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x25mm button-head machine (hex drive) (6) Screws, 3x30mm button-head machine (hex drive) (6) Screws, 3x8mm caphead machine (hex drive) (6) Screws, 3x8mm countersunk machine (6) (hex drive) Screws, 4x10mm button-head machine (hex drive) (6) Screws, 4x12mm button-head machine (hex drive) (6) Screws, 4x14mm button-head machine (hex drive) (6) Screws, 4x14mm button-head machine (hex drive) (6) Screws, 4x20mm button-head machine (hex drive) (6) Screws, 4x20mm button-head machine (hex drive) (6) Screws, 4x25mm button-head machine (hex drive) (6) |
| 8920 8932X 8932A 8932A 8932R 8932 8916 8958 8947 8938X 8946 8937X 8937G 8937A 8937A 8937R 8937 10230-BLUI 10230-GRN | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) Bulkhead, front (upper and lower) Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), left & right Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear (2) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X, 8997A, 8997G, 8997R, 8997X) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Shock tower, front (left & right halves) Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Suspension arms, lower, black (left and right, front or rear) (2) | 8447R 8447 5147X 3236 2577 2587 2551 2578 2579 2553 3646 2583 2581 2582 2657 2550 3936 2535 3937 3938 3933 2589 2455 2596 2595 8940X | serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Nuts, 5mm flanged nylon locking (steel, serrated) (8) Screws, 2.5x12mm cap-head machine (6) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x10mm caphead machine (6) (no washer) Screws, 3x12mm button-head machine (6) (hex drive) Screws, 3x12mm button-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x15mm countersunk machine (6) (hex drive) Screws, 3x15mm flat-head machine (hex drive) (6) Screws, 3x25mm button-head machine (hex drive) (6) Screws, 3x25mm button-head machine (hex drive) (6) Screws, 3x30mm button-head machine (hex drive) (6) Screws, 3x8mm caphead machine (hex drive) (6) Screws, 3x8mm countersunk machine (6) (hex drive) Screws, 4x10mm button-head machine (hex drive) (6) Screws, 4x10mm countersunk machine (hex drive) (6) Screws, 4x12mm button-head machine (hex drive) (6) Screws, 4x16mm button-head machine (hex drive) (6) Screws, 4x20mm button-head machine (hex drive) (6) Screws, 4x20mm button-head machine (hex drive) (6) Screws, 4x25mm button-head machine (hex drive) (6) |
| 8920 8932X 8932A 8932A 8932R 8932 8916 8958 8947 8938X 8946 8937X 8937G 8937A 8937A 8937R 8937 10230 10230-BLUI 10230-GRN | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) Bulkhead, front (upper and lower) Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), left & right Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear (2) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X, 8997A, 8997G, 8997R, 8997X) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Shock tower, front (left & right halves) Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (orange-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Steering blocks, left & right Suspension arms, lower, black (left and right, front or rear) (2) Suspension arms, lower, black (left and right, front or rear) (2) | 8447R 8447 5147X 3236 2577 2587 2551 2578 2579 2553 3646 2583 2581 2582 2657 2550 3936 2535 3937 3938 3933 2589 2455 2596 2595 8940X | serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Nuts, 5mm flanged nylon locking (steel, serrated) (8) Screws, 2.5x12mm cap-head machine (6) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x10mm caphead machine (6) (no washer) Screws, 3x10mm countersunk machine (6) (hex drive) Screws, 3x12mm button-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x15mm countersunk machine (6) (hex drive) Screws, 3x15mm dlat-head machine (hex drive) (6) Screws, 3x25mm button-head machine (hex drive) (6) Screws, 3x25mm button-head machine (hex drive) (6) Screws, 3x30mm button-head machine (hex drive) (6) Screws, 3x8mm caphead machine (hex drive) (6) Screws, 4x10mm button-head machine (hex drive) (6) Screws, 4x12mm button-head machine (hex drive) (6) Screws, 4x14mm button-head machine (hex drive) (6) Screws, 4x20mm button-head machine (hex drive) (6) Screws, 4x25mm button-head machine (hex drive) (6) Screws, 4x25mm button-head machine (hex drive) (6) Screws, 4x35mm button-head machine (hex drive) (6) Screws, 4x35mm button-head machine (hex drive) (6) Suspension pin set, complete (hardened steel), 4x64mm (4), 4x32mm (4), 4x33mm (4), 4x33mm (4), 4x47mm (4)/ 3x8mm BCS (14)/ 3x6mm BCS (4)/ retainers (8) Suspension pin set, front (left or right) (hardened steel), 4x64mm (1), 4x22mm (2), 4x38mm (1), 4x33mm (1), 4x47mm (1) Suspension pin set, rear (left or right) (hardened steel), |
| 8920 8932X 8932A 8932A 8932R 8932 8916 8958 8947 8938X 8946 8937X 8937G 8937A 8937A 8937A 10230 10230-BLUI 10230-GRN 10230-RED | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) Bulkhead, front (upper and lower) Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), left & right Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear (2) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X, 8997A, 8997G, 8997R, 8997X) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Shock tower, front (left & right halves) Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Suspension arms, lower, black (left and right, front or rear) (2) Suspension arms, lower, orange (left and right, front or rear) (2) Suspension arms, lower, orange (left and right, front or rear) (2) | 8447R 8447 5147X 3236 2577 2587 2551 2578 2579 2553 3646 2583 2581 2582 2657 2550 3936 2535 3937 3938 3933 2589 2455 2596 2595 8940X | serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Nuts, 5mm flanged nylon locking (steel, serrated) (8) Screws, 2.5x12mm cap-head machine (6) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x10mm caphead machine (6) (no washer) Screws, 3x12mm button-head machine (6) (hex drive) Screws, 3x12mm button-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x15mm countersunk machine (6) (hex drive) Screws, 3x15mm flat-head machine (hex drive) (6) Screws, 3x25mm button-head machine (hex drive) (6) Screws, 3x25mm button-head machine (hex drive) (6) Screws, 3x30mm button-head machine (hex drive) (6) Screws, 3x8mm caphead machine (hex drive) (6) Screws, 3x8mm countersunk machine (6) (hex drive) Screws, 4x10mm button-head machine (hex drive) (6) Screws, 4x10mm countersunk machine (hex drive) (6) Screws, 4x12mm button-head machine (hex drive) (6) Screws, 4x16mm button-head machine (hex drive) (6) Screws, 4x20mm button-head machine (hex drive) (6) Screws, 4x20mm button-head machine (hex drive) (6) Screws, 4x25mm button-head machine (hex drive) (6) |
| 8920 8932X 8932A 8932A 8932R 8932 8916 8958 8947 8938X 8946 8937X 8937G 8937A 8937A 8937A 8937A 10230-BLUI 10230-GRN 10230-GRN 10230-RED 8929 | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) Bulkhead, front (upper and lower) Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), left & right Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear (2) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X, 8997A, 8997G, 8997R, 8997X) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Shock tower, front (left & right halves) Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Suspension arms, lower, black (left and right, front or rear) (2) Suspension arms, lower, orange (left and right, front or rear) (2) Suspension arms, lower, orange (left and right, front or rear) (2) Suspension arms, lower, red (left and right, front or rear) (2) | 8447R 8447 5147X 3236 2577 2587 2551 2578 2579 2553 3646 2583 2581 2582 2657 2550 3936 2535 3937 3938 3933 2589 2455 2596 2595 8940X | serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Nuts, 5mm flanged nylon locking (steel, serrated) (8) Screws, 2.5x12mm cap-head machine (6) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x10mm caphead machine (6) (no washer) Screws, 3x10mm countersunk machine (6) (hex drive) Screws, 3x12mm button-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x15mm countersunk machine (6) (hex drive) Screws, 3x15mm dlat-head machine (hex drive) (6) Screws, 3x25mm button-head machine (hex drive) (6) Screws, 3x25mm button-head machine (hex drive) (6) Screws, 3x30mm button-head machine (hex drive) (6) Screws, 3x8mm caphead machine (hex drive) (6) Screws, 4x10mm button-head machine (hex drive) (6) Screws, 4x12mm button-head machine (hex drive) (6) Screws, 4x14mm button-head machine (hex drive) (6) Screws, 4x20mm button-head machine (hex drive) (6) Screws, 4x25mm button-head machine (hex drive) (6) Screws, 4x25mm button-head machine (hex drive) (6) Screws, 4x35mm button-head machine (hex drive) (6) Screws, 4x35mm button-head machine (hex drive) (6) Suspension pin set, complete (hardened steel), 4x64mm (4), 4x32mm (4), 4x33mm (4), 4x33mm (4), 4x47mm (4)/ 3x8mm BCS (14)/ 3x6mm BCS (4)/ retainers (8) Suspension pin set, front (left or right) (hardened steel), 4x64mm (1), 4x22mm (2), 4x38mm (1), 4x33mm (1), 4x47mm (1) Suspension pin set, rear (left or right) (hardened steel), |
| 8920 8932X 8932A 8932A 8932R 8932 8916 8958 8947 8938X 8946 8937X 8937G 8937A 8937A 8937A 10230 10230-BLUI 10230-GRN 10230-RED | Bulkhead tie bar, front, upper (1)/ lower (2) (steel) Bulkhead, front (upper and lower) Caster blocks (c-hubs), 6061-T6 aluminum (blue-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (green-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (orange-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), 6061-T6 aluminum (red-anodized), left & right/ 4x22mm pin (4)/ 3x6mm BCS (4)/ retainers (4) Caster blocks (c-hubs), left & right Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or rear (2) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X, 8997A, 8997G, 8997R, 8997X) Servo horn, steering/ linkage, steering (46mm, assembled with pivot balls) Shock tower, front (left & right halves) Steering bellcranks/ bellcrank support/ servo saver/ servo saver spring/ draglink/ 3x20mm shoulder screws (2) Steering blocks, 6061-T6 aluminum (blue-anodized), left & right Steering blocks, 6061-T6 aluminum (green-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, 6061-T6 aluminum (red-anodized), left & right Steering blocks, left & right Suspension arms, lower, black (left and right, front or rear) (2) Suspension arms, lower, orange (left and right, front or rear) (2) Suspension arms, lower, orange (left and right, front or rear) (2) | 8447R 8447 5147X 3236 2577 2587 2551 2578 2579 2553 3646 2583 2581 2582 2657 2550 3936 2535 3937 3938 3933 2589 2455 2596 2595 8940X | serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) Nuts, 5mm flanged nylon locking (steel, black serrated) (8) Nuts, 5mm flanged nylon locking (steel, serrated) (8) Screws, 2.5x12mm cap-head machine (6) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x10mm caphead machine (6) (no washer) Screws, 3x10mm countersunk machine (6) (hex drive) Screws, 3x12mm button-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x15mm countersunk machine (6) (hex drive) Screws, 3x15mm dlat-head machine (hex drive) (6) Screws, 3x25mm button-head machine (hex drive) (6) Screws, 3x25mm button-head machine (hex drive) (6) Screws, 3x30mm button-head machine (hex drive) (6) Screws, 3x8mm caphead machine (hex drive) (6) Screws, 4x10mm button-head machine (hex drive) (6) Screws, 4x12mm button-head machine (hex drive) (6) Screws, 4x14mm button-head machine (hex drive) (6) Screws, 4x20mm button-head machine (hex drive) (6) Screws, 4x25mm button-head machine (hex drive) (6) Screws, 4x25mm button-head machine (hex drive) (6) Screws, 4x35mm button-head machine (hex drive) (6) Screws, 4x35mm button-head machine (hex drive) (6) Suspension pin set, complete (hardened steel), 4x64mm (4), 4x32mm (4), 4x33mm (4), 4x33mm (4), 4x47mm (4)/ 3x8mm BCS (14)/ 3x6mm BCS (4)/ retainers (8) Suspension pin set, front (left or right) (hardened steel), 4x64mm (1), 4x22mm (2), 4x38mm (1), 4x33mm (1), 4x47mm (1) Suspension pin set, rear (left or right) (hardened steel), |

| Page 3 Max | xx® Slash®: ˈ | TQi™ Traxxas Link | ™ Enabled 2.4GHz | Radio & TSM® | (Model 102076-4) | Parts List |
|------------|---------------|-------------------|------------------|--------------|------------------|------------|
|------------|---------------|-------------------|------------------|--------------|------------------|------------|

| | LED Lights | 6521 | Sensor, temperature and voltage (long) |
|------------------|--|--------------|---|
| 590 | High-Voltage Power Amplifier | 2091 | Servo case/ gaskets (for 2090 waterproof servo) |
| 884 | LED light bar, front (high-voltage) (40 white LEDs (double row), | 2090 | Servo, digital high-torque (ball bearing), waterproof |
| 004 | 82mm wide) (fits Maxx®, X-Maxx®, or XRT™) | 6553X | Telemetry Expander 2.0 and GPS module 2.0, TQi radio syste |
| 383 | LED light bar, rear, red (with white reverse light) (high-voltage) | 6550X | Telemetry expander 2.0, TQi radio system (for use only with |
| 505 | (24 red LEDs, 24 white LEDs, 100mm wide)/ light bar mount | | #6551X GPS module) |
| | (fits Maxx®, X-Maxx®, or XRT™) | 6551X | Telemetry GPS module 2.0, TQi radio system (for use only wi |
| 0290 | LED light kit, Maxx Slash®, complete (includes #6590 high- | | #6550X telemetry expander) |
| | voltage power amplifier) | 6509R | TQi 2.4 GHz High Output radio system, 2-channel, Traxxas® Link |
| | | | enabled, TSM® (2-ch transmitter, 5-ch micro receiver) |
| | Motors & Electronics | 6507R | TQi 2.4 GHz High Output radio system, 4-channel with |
| 49 | Adapter, standard servo (adapts standard servo to fit in X- | | Traxxas® Link Bluetooth® module, TSM® (4-ch transmitter, § |
| | Maxx®)Adapter, standard servo (adapts standard servo to fit in | 0.500 | ch micro receiver) |
| | Maxx®, X-Maxx®, or XRT®) | 6528 | Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 2- |
| 87 | Covers, gear (2) | 0.500 | channel (transmitter only) |
| 92 | Gear set (for 2090 servo) | 6529 | Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output |
| 260 | Motor mount cap | 6530 | 3-channel (transmitter only) |
| 60 | Motor mounts (front and rear)/ 4x10 BCS with split and flat washers | 6530 | Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output 4-channel (transmitter only) |
| | (1)/ pin (1) | CE11 | ` -, |
| 60X | Motor mounts (front and rear)/ 4x10 BCS with split and flat | 6511 | Traxxas® Link Bluetooth® module |
| | washers (1)/ pin (1) (for installation of #3481 motor into Maxx®) | | Ready-To-Race Model |
| 83 | Motor, 2000Kv 77mm, brushless (with 6.5mm gold-plated | 102076-4 | Maxx® Slash®: 1/10 Scale 4WD Brushless Electric Short Course |
| | connectors & high-efficiency heatsink) | | Racing Truck with TQi™ Traxxas Link™ Enabled 2.4GHz Radio |
| 83R | Rebuild kit, 2000Kv motor, brushless (includes plastic endbell, | | System & Traxxas Stability Management (TSM)® |
| | 5x16x5mm ball bearings (2), 5.05x7.5x.05 washer (1), | | Rear Suspension |
| | 5.05x7.5x0.1 washer (1), 5.05x7.5x.19 washer (1), 6x5x8.5 | 2007 | |
| 01 | spacer (1)) | 8927 | Bulkhead tie bar, rear, upper (1)/ lower front (1)/ lower rear (1) |
| 91 47V | Servo case/ gaskets (for 2090 waterproof servo) | 0000 | (steel) |
| 47X | Servo horn, steel | 8928 | Bulkhead, rear (upper and lower) |
| 47 | Servo horn, steering/ linkage, steering (46mm, assembled with | 8952X | Carriers, stub axle (blue-anodized 6061-T6 aluminum) (rear) |
| | pivot balls) | 8952G | Carriers, stub axle (green-anodized 6061-T6 aluminum) (rear |
| 90 | Servo, digital high-torque (ball bearing), waterproof | | (2) |
| 85 | Servo, digital high-torque (ball bearing), waterproof | 8952 | Carriers, stub axle (left & right) |
| 85X | Servo, digital high-torque, metal gear (ball bearing), | 8952A | Carriers, stub axle (orange-anodized 6061-T6 aluminum) (rea |
| | waterproof/ servo saver spring/ steering link | | (2) |
| 85R | Servo, digital high-torque/high-speed, metal gear (ball | 8952R | Carriers, stub axle (red-anodized 6061-T6 aluminum) (rear) (2 |
| | bearing), waterproof | 8916 | Mount, tie bar, front (1)/ rear (1)/ suspension pin retainer, front or |
| 84 | Velineon® VXL-6s Brushless Power System, waterproof (includes | | rear (2) |
| | VXL-6s ESC and 2000Kv, 77mm motor) | 8958 | Rod ends (4) (assembled with steel pivot balls) (replacement |
| 85T | Velineon® VXL-6s Electronic Speed Control, waterproof | | ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X |
| | (brushless) (fwd/rev/brake) | - | 8997A, 8997G, 8997R, 8997X) |
| | Radio System, Batteries & Chargers | 10234 | Shock mount, lower (extended travel, left & right/ 3x18mm BCS (|
| 72X | 5000mah 11.1v 3-Cell 25C LiPo Battery | 8939X | Shock tower, rear (left & right halves) |
| 89X | 5000mah 14.8v 4-Cell 25C LiPo Battery (long) | 10230 | Suspension arms, lower, black (left and right, front or rear) (2) |
| 57X | 6400mah 11.1v 3-Cell 25C LiPo Battery | 10230-BLUE | Suspension arms, lower, blue (left and right, front or rear) (2) |
| 14 | AA 4PK | 10230-GRN | Suspension arms, lower, green (left and right, front or rear) (|
| 38X | Adapter, Traxxas® iD® LiPo battery (adapts Traxxas® iD® | 10230-ORNG | Suspension arms, lower, orange (left and right, front or rear) |
| 307 | batteries to separate balance ports) | | (2) |
| 26 | Antenna caps, vinyl (2)/ antenna spool | 10230-RED | Suspension arms, lower, red (left and right, front or rear) (2) |
| 26 | | 8929 | Suspension arms, upper, black (left or right, front or rear) (2) |
| | Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) | 8929X | Suspension arms, upper, blue (left or right, front or rear) (2) |
| 26A | Antenna, tube, black (1)/ vinyl antenna cap (1)/ wire retainer (1) | 8929G | Suspension arms, upper, green (left or right, front or rear) (2 |
| 43 | Battery charge indicators, green (4), grey (4), blue (4) | 8929T | Suspension arms, upper, orange (left or right, front or rear) (|
| 48 | Battery door, TQ 2.4 transmitter (replacement for #6516, 6517 | 8929R | Suspension arms, upper, red (left or right, front or rear) (2) |
| 00 | transmitter) | 8929A | Suspension arms, upper, white (left or right, front or rear) (2) |
| 90 | Battery/charger completer pack (includes #2972 Dual iD | 7743 | Suspension pin retainer (4) |
| | charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo iD® Battery | 7743-BLUE | Suspension pin retainer, 6061-T6 aluminum (blue-anodized) |
| 72 | (2)) Chargor E7 Book Dual 100W NiMH/LiPo with iD Auto Battory | 7743-GRAY | Suspension pin retainer, 6061-T6 aluminum (gray-anodized) |
| 72 | Charger, EZ-Peak Dual, 100W, NiMH/LiPo with iD Auto Battery Identification | 7743-GRN | Suspension pin retainer, 6061-T6 aluminum (green-anodized |
| 72 | | | (4) |
| 73 | Charger, EZ-Peak Live Dual, 200W, NiMH/LiPo with iD Auto | 7743-ORNG | Suspension pin retainer, 6061-T6 aluminum (orange-anodize |
| 70 | Battery Identification Charger E7 Book Blue 4 amp NiMH/I iBo with iD Auto Bettery | | (4) |
| 70 | Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with iD Auto Battery | 7743-RED | Suspension pin retainer, 6061-T6 aluminum (red-anodized) (4 |
| 81 | Identification Charger, EZ-Peak® Plus 4s, 8 amp, NiMH/LiPo with iD® Auto | 8940X | Suspension pin set, complete (hardened steel), 4x64mm (4), |
| J 1 | Battery Identification | | 4x22mm (4), 4x38mm (4), 4x33mm (4), 4x47mm (4)/ 3x8mm |
| 25 | Communication link, telemetry expander | | BCS (14)/ 3x6mm BCS (4)/ retainers (8) |
| 2 5 27 | Connector, 25.2 volt to 14.8 volt jumper (allows a Traxxas® dual- | 8943 | Suspension pin set, rear (left or right) (hardened steel), |
| <u> </u> | battery 25.2 ESC to run on a single 14.8V battery pack) | - | 4x64mm (1), 4x38mm (1), 4x33mm (1), 4x47mm (1) |
| 71 | EZ-Peak Live 12-amp NiMH/LiPo Fast Charger with iD® Auto | 8941 | Suspension pins, lower, inner (front or rear), 4x64mm (2) (harden |
| | Battery Identification and Bluetooth® | | steel) |
| 92 | | 8940 | Suspension screw pin set, front or rear (hardened steel), 4x18mn |
| | Gear set (for 2090 servo) | - | (4), 4x38mm (2), 4x33mm (2), 4x43mm (2) |
| 68X | LiPo cell voltage checker/balancer (includes #2938X adapter | | |
| 60 | for Traxxas® iD® batteries) | | Shock Oil |
| 68 | LiPo cell voltage checker/balancer (requires #2938X adapter | 5031 | Oil, shock (20 wt, 200 cSt, 60cc) (silicone) |
| | for Traxxas® iD® batteries) | 5032 | Oil, shock (30 wt, 350 cSt, 60cc) (silicone) |
| 35 | Mount, temperature sensor (electric motors)/ wire tie/ thermal | 5033 | Oil, shock (40 wt, 500 cSt, 60cc) (silicone) |
| 00 | pad | 5034 | Oil, shock (50 wt, 600 cSt, 60cc) (silicone) |
| 33 | Receiver, micro, TQi 2.4GHz with telemetry & TSM® (5-channel) | 5035 | Oil, shock (60 wt, 700 cSt, 60cc) (silicone) |
| 52 | Seal kit, expander box (includes o-ring, seals, and silicone | 5036 | Oil, shock (70 wt, 900 cSt, 60cc) (silicone) |
| | grease) | | |
| | = - | 5037 | Oll. Shock (ou wt. 1.000 car. bucci (shicone) |
| 526 527 | Sensor, auto-detectable, temperature Sensor, auto-detectable, voltage | 5037 5029 | Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone) Shock oil bottle (60cc) (for mixing shock oil) |

| Page 4 | Maxx® Slash®: | TQi™ Traxxas | Link™ Enabled 2.4 | GHz Radio & TSM® | (Model 102076-4) | Parts List |
|--------|---------------|--------------|-------------------|------------------|------------------|------------|
|--------|---------------|--------------|-------------------|------------------|------------------|------------|

| 5038X 5038 | Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack) Spinning carousel rack | 8948X | Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) |
|----------------------|--|----------------------|---|
| | Shocks (GT-Maxx®) | 8948G | Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod |
| 8965X | Body, GT-Maxx® shock (aluminum, blue-anodized) (1) | | ends, front (4)/ aluminum wrench (1) |
| 8965G | Body, GT-Maxx® shock (aluminum, green-anodized) (1) | 8948A | Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, |
| 8965T 8965R | Body, GT-Maxx® shock (aluminum, orange-anodized) (1) | | stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod |
| 8962 | Body, GT-Maxx® shock (aluminum, red-anodized) (1) Rebuild kit, GT-Maxx® shocks (lower cartridge, pistons, piston | 8948R | ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, |
| 0902 | nuts, bladders, screws) (renews 2 shocks) | 0340K | stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod |
| 8964X | Shock caps, aluminum (blue-anodized), GT-Maxx®, shocks (4) | | ends, front (4)/ aluminum wrench (1) |
| 8964G | Shock caps, aluminum (green-anodized), GT-Maxx® shocks (4) | 8948 | Toe links, molded composite, 100mm (89mm center to center) |
| 8964T | Shock caps, aluminum (orange-anodized), GT-Maxx® shocks | | (black) (2) |
| | (4) | | Suspension Linkage |
| 8964R | Shock caps, aluminum (red-anodized), GT-Maxx® shocks (4) | 8958 | Rod ends (4) (assembled with steel pivot balls) (replacement |
| 8964 | Shock caps, GT-Maxx® shocks/ spring perch/ adjusters (2) (for 2 | 0330 | ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X, |
| 0000 | shocks) | | 8997A, 8997G, 8997R, 8997X) |
| 8963 | Shock shaft, 72mm (GT-Maxx®) (steel, chrome finish) (2)/ rod ends | 7743 | Suspension pin retainer (4) |
| 8963T | (2)/ hollow balls (2) Shock shoft, 72mm (CT Maxx®) (TiN costed) (2) (cosembled) | 7743-BLUE | Suspension pin retainer, 6061-T6 aluminum (blue-anodized) (4) |
| 03031 | Shock shaft, 72mm (GT-Maxx®) (TiN-coated) (2) (assembled with rod ends and steel hollow balls) | 7743-GRAY | Suspension pin retainer, 6061-T6 aluminum (gray-anodized) (4) |
| 9660 | Shocks, GT-Maxx®, aluminum (blue-anodized) (fully assembled | 7743-GRN | Suspension pin retainer, 6061-T6 aluminum (green-anodized) |
| 0000 | w/o springs) (2) | | (4) |
| 8961G | Shocks, GT-Maxx®, aluminum (green-anodized) (fully assembled | 7743-ORNG | Suspension pin retainer, 6061-T6 aluminum (orange-anodized) |
| | w/o springs) (2) | == 40 DED | (4) |
| 8961T | Shocks, GT-Maxx®, aluminum (orange-anodized) (fully assembled | 7743-RED | Suspension pin retainer, 6061-T6 aluminum (red-anodized) (4) |
| | w/o springs) (2) | 8940X | Suspension pin set, complete (hardened steel), 4x64mm (4), 4x22mm (4), 4x38mm (4), 4x33mm (4), 4x47mm (4)/ 3x8mm |
| 8961R | Shocks, GT-Maxx®, aluminum (red-anodized) (fully assembled w/o | | BCS (14)/ 3x6mm BCS (4)/ retainers (8) |
| 0000 | springs) (2) | 8942 | Suspension pin set, front (left or right) (hardened steel), |
| 8968X | Spring retainer (adjuster), blue-anodized aluminum, GT-Maxx® | | 4x64mm (1), 4x22mm (2), 4x38mm (1), 4x33mm (1), 4x47mm (1) |
| 8968G | shocks (4) (assembled with o-ring Spring retainer (adjuster), green-anodized aluminum, GT- | 8943 | Suspension pin set, rear (left or right) (hardened steel), |
| 03000 | Maxx® shocks (4) (assembled with o-ring) | | 4x64mm (1), 4x38mm (1), 4x33mm (1), 4x47mm (1) |
| 8968A | Spring retainer (adjuster), orange-anodized aluminum, GT- | 8941 | Suspension pins, lower, inner (front or rear), 4x64mm (2) (hardened |
| | Maxx® shocks (4) (assembled with o-ring) | | steel) |
| 8968R | Spring retainer (adjuster), red-anodized aluminum, GT-Maxx® | 8940 | Suspension screw pin set, front or rear (hardened steel), 4x18mm |
| | shocks (4) (assembled with o-ring) | 0040V | (4), 4x38mm (2), 4x33mm (2), 4x43mm (2) |
| 10240 | Springs, shock (natural finish) (GT-Maxx®) (1.036 rate) (2) | 8948X | Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod |
| 10241 | Springs, shock (natural finish) (GT-Maxx®) (1.150 rate, white | | ends, front (4)/ aluminum wrench (1) |
| | stripe) (2) | 8948G | Toe links, front (TUBES green-anodized, 7075-T6 aluminum, |
| 10242 | Springs, shock (natural finish) (GT-Maxx®) (1.350 rate, brown | | stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod |
| 10040 | stripe) (2) | | ends, front (4)/ aluminum wrench (1) |
| 10243 | Springs, shock (natural finish) (GT-Maxx®) (1.400 rate, blue stripe) (2) | 8948A | Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, |
| | | l | stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod |
| | Spur Gears & Pinion Gears | 00400 | ends, front (4)/ aluminum wrench (1) |
| 6487X | Gear, 15-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw | 8948R | Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod |
| C400V | (for use only with steel spur gears) | | ends, front (4)/ aluminum wrench (1) |
| 6489X | Gear, 16-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw | 8948 | Toe links, molded composite, 100mm (89mm center to center) |
| 6490X | (for use only with steel spur gears) Gear, 17-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw | | (black) (2) |
| 04307 | (for use only with steel spur gears) | | Team Traxxas Items |
| 6491X | Gear, 18-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw | 0544 | |
| 0-10-170 | (for use only with steel spur gears) | 2514 | Decal sheet, racing sponsors |
| 6491R | Gear, 18-T pinion (machined) (1.0 metric pitch) (fits 5mm | 9950 | Official Team Traxxas® racing decal set(flag logo/ 6-color) |
| | shaft)/ set screw (for use only with steel spur gears) | 9909 | Traxxas® racing banner, red & black (3x7 feet) |
| 6494X | Gear, 20-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw | | Tires & Wheels |
| | (for use only with steel spur gears) | 8447A | Nuts, 5mm flanged nylon locking (aluminum, black-anodized, |
| 6495X | Gear, 22-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw | | serrated) (4) |
| C40CY | (for use only with steel spur gears) | 8447X | Nuts, 5mm flanged nylon locking (aluminum, blue-anodized, |
| 6496X | Gear, 24-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears) | 04470 | serrated) (4) |
| 6492X | Gear, 25-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for | 8447G | Nuts, 5mm flanged nylon locking (aluminum, green-anodized, |
| O 7 3∠∧ | use only with steel spur gears) | 9447D | serrated) (4) |
| 6497 | Gear, 26-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw | 8447R | Nuts, 5mm flanged nylon locking (aluminum, red-anodized, serrated) (4) |
| | cour, zo : p.mon (no mouno prion, (no omm onun), cor coron | 8447 | Nuts, 5mm flanged nylon locking (steel, black serrated) (8) |
| 6442 | Spur gear, 46-tooth (machined, hardened steel) (wide face, 1.0 | 5147X | Nuts, 5mm flanged nylon locking (steel, serrated) (8) |
| | metric pitch) | 10272 | Tires & wheels, assembled, glued, left (1), right (1) (black wheels, |
| 6447R | Spur gear, 46-tooth, steel (wide-face, 1.0 metric pitch) | | Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® |
| 6443 | Spur gear, 50-tooth (machined, hardened steel) (wide face, 1.0 | | rated) |
| 04405 | metric pitch) | 10272-BLK | Tires & wheels, assembled, glued, left (1), right (1) (black with |
| 6448R | Spur gear, 50-tooth, steel (wide-face, 1.0 metric pitch) | | satin beadlock wheels, Maxx Slash® belted tires, foam inserts) |
| 6444 | Spur gear, 54-tooth (machined, hardened steel) (wide face, 1.0 | 40070 0041 | (17mm splined) (TSM® rated) |
| 6440B | metric pitch) Spur gear, 54-tooth, steel (wide-face, 1.0 metric pitch) | 10272-GRAY | Tires & wheels, assembled, glued, left (1), right (1) (charcoal |
| | | | gray wheels, Maxx Slash® belted tires, foam inserts) (17mm splined) (TSM® rated) |
| 6449R | Secretaria de la Contrata de C | 40070 | Tires, Maxx Slash® (belted) (2)/ foam inserts (2) |
| 0443K | Steering Components | 10270 | |
| 7020 | Ball bearings, blue rubber sealed (8x12x3.5mm) (2) | 10270 8956 | |
| 7020 8947X | Ball bearings, blue rubber sealed (8x12x3.5mm) (2) Servo horn, steel | 8956 8956X | Wheel hubs, hex (2)/ 2.5x14 pins (2) |
| 7020 | Ball bearings, blue rubber sealed (8x12x3.5mm) (2) Servo horn, steel Servo horn, steering/ linkage, steering (46mm, assembled with | 8956 | |
| 7020 8947X | Ball bearings, blue rubber sealed (8x12x3.5mm) (2) Servo horn, steel | 8956 | Wheel hubs, hex (2) 2.5x14 pins (2) Wheel hubs, hex, aluminum (blue-anodized) (4)/ 4x13mm screw |

| Page 5 | Maxx® Slash®: TQi™ Traxxas Link™ Enabled 2.40 | GHz Radio | o & TSM® (Model 102076-4) Parts List |
|----------------------|---|-----------|--|
| 8956T | Wheel hubs, hex, aluminum (orange-anodized) (4)/ 4x13mm screw pins (4) | | Turnbuckles & Threaded Rods |
| 8956R | Wheel hubs, hex, aluminum (red-anodized) (4)/ 4x13mm screw pins (4) | 8948X | Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod |
| 8654 | Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) | 8948G | ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES green-anodized, 7075-T6 aluminum, |
| 8654-GRAY | Wheel hubs, splined, 17mm (gray-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) | | stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) |
| 8654G | Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) | 8948A | Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod |
| 8654A | Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5mm GS (4)/ 3x14mm pin (4) | 8948R | ends, front (4)/ aluminum wrench (1) Toe links, front (TUBES red-anodized, 7075-T6 aluminum, |
| 8654R | Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4), 3x14mm pin (4) | 00.40 | stronger than titanium) (88mm) (2)/ rod ends, rear (4)/ rod ends, front (4)/ aluminum wrench (1) |
| 8957 10257 | Wheel washers (4) Wheel washers (4) | 8948 | Toe links, molded composite, 100mm (89mm center to center) (black) (2) |
| 8957X | Wheel washers, blue (4) | | |
| 8957G 8957T | Wheel washers, green (4) Wheel washers, orange (4) | | |
| 8957R | Wheel washers, red (4) | | If you have questions or need technical assistance, call Traxxas at: |
| 10271 | Wheels (black) (2) | | 1-888-TRAXXAS |
| 8987 | Transmission Components | | (1-888-872-9927) (U.S. residents only) |
| 8985 | Covers, gear (2) Input gear, transmission, 22-tooth/ 2.5x12mm pin | | For orders, calls outside the U.S., and other information, call 972-549-3000, or fax to 972-549-3011 e-mail Traxxas at support@Traxxas.com |
| 8986 | Input shaft, transmission | | TRAXXAS.COM |
| 5040 | Oil, differential (20M wt) (standard) | | |
| | Traxxas Tools | | |
| 3/33X | Rody reamer (aluminum handle) | | |

| 3040 | Oil, differential (2011 wt) (standard) |
|-------|---|
| | Traxxas Tools |
| 3433X | Body reamer (aluminum handle) |
| 3433 | Body reamer (plastic handle) |
| 3436 | Cap, body reamer |
| 3432 | Scissors, curved tip |
| 3431 | Scissors, straight tip |
| 8712 | Speed Bit Essentials Set, hex and nut driver, 7-piece, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm, and 8.0mm), 1/4" drive |
| 8720 | Speed bit handle, large (overmolded) |
| 8721 | Speed bit handle, medium (one piece) |
| 8722 | Speed bit handle, premium (rubber overmold) |
| 8710 | Speed Bit Master Set, hex and nut driver, 13-piece, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm), (ball-end: 2.0mm, 2.5mm, 3.0mm), and nut drivers (4.0mm, 4.5mm, 5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive |
| 8711 | Speed Bit Master Set, hex driver, 7-piece straight and ball end, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm) (ball end: 2.0mm, 2.5mm, 3.0mm), 1/4" drive |
| 8719 | Speed Bit Master Set, nut driver, 6-piece, includes premium handle (medium), travel pouch, and nut drivers (4.0mm, 4.5mm, 5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive |
| 8716 | Speed Bit Set, hex driver, 2-piece ball-end (2.0mm, 2.5mm), 1/4" drive |
| 8716X | Speed Bit Set, hex driver, 3-piece ball-end (2.0mm, 2.5mm, 3.0mm) 1/4" drive |
| 8715 | Speed Bit Set, hex driver, 3-piece straight (1.5mm, 2.0mm, 2.5mm), 1/4" drive |
| 8715X | Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm, 2.5mm, 3.0mm), 1/4" drive |
| 8714 | Speed Bit Set, screwdriver, 3-piece straight (3mm slotted, #1 Phillips, and #2 Phillips bits), 1/4" drive |
| 2748R | Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint wrench) |
| 3415 | Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrenches/ driver handle) |

REV. 240327 1251